

# Information of Discontinued Models

Thru-beam type fiber • Reflective type fiber  
(Changed to 2 m 6.562 ft free-cut type)

Stopping taking order date:

30, Sep, 2005

Date of production discontinuance: 31, Dec, 2005

## Advantages of switching to recommended replacements

















### Free-cut

The fiber that previously had a fixed length of 500 mm 19.685 in. But now it is provided in a free-cut length of 2 m 6.562 ft, so that the length can be adjusted as desired to suit the setup location. In addition, an attachment that allows two cables to be joined together at the ends is also provided, making installation even smoother.

## Main points of difference between recommended replacements and discontinued models

Discontinued models	Recommended replacements	Main points of difference from discontinued models
<b>• Thru-beam type fiber</b>		
Model No.	Model No.	
FT-500	FT-FM2	<ul style="list-style-type: none"> <li>The discontinued model has a fiber length of 500 mm 19.685 in and a plug length of 19 mm 0.748 in. The recommended replacement is a 2 m 6.562 ft free-cut type.</li> </ul>
FT-500S	FT-FM2S	
FT-500S4	FT-FM2S4	
FT-N500	FT-NFM2	
FT-N500S	FT-NFM2S	
FT-N500S4	FT-NFM2S4	
FT-S500	FT-SFM2	
FT-SN500	FT-SNFM2	
<b>• Reflective type fiber</b>		
Model No.	Model No.	
FD-500	FD-FM2	<ul style="list-style-type: none"> <li>The discontinued model has a fiber length of 500 mm 19.685 in (FD-SNM1SV2: 1 m 3.281 ft) and a plug length of 19 mm 0.748 in. The recommended replacement is a 2 m 6.562 ft free-cut type.</li> <li>Note: The discontinued model (FD-SNM1SV2) has a fiber length of 1 m 3.281 ft, a sleeve length of 20 mm 0.787 in and shape of fiber head of <math>\phi 1.5</math> mm <math>\phi 0.059</math> in. The recommended replacement (FD-V41) is a 2 m 6.562 ft free-cut type with a sleeve length of 10 mm 0.394 in and shape of fiber head of <math>\phi 1.5</math> mm <math>\phi 0.059</math> in.</li> </ul>
FD-500S	FD-FM2S	
FD-500S4	FD-FM2S4	
FD-G500	FD-G4	
FD-N500	FD-NFM2	
FD-N500S	FD-NFM2S	
FD-N500S4	FD-NFM2S4	
FD-SN500	FD-SNFM2	
FD-SNM1SV2	FD-V41 (Note)	

## Shape of fiber head

Type	Discontinued models		Recommended replacements	
	Shape of fiber head (mm in)	Model No.	Shape of fiber head (mm in)	Model No.
Thru-beam type fiber	Lens mountable	 FT-500	Lens mountable	 FT-FM2
	Sleeve 90 mm 3.543 in	 FT-500S	Sleeve 90 mm 3.543 in	 FT-FM2S
	Sleeve 40 mm 1.575 in	 FT-500S4	Sleeve 40 mm 1.575 in	 FT-FM2S4
		 FT-N500		 FT-NFM2
	Sleeve 90 mm 3.543 in	 FT-N500S	Sleeve 90 mm 3.543 in	 FT-NFM2S
	Sleeve 40 mm 1.575 in	 FT-N500S4	Sleeve 40 mm 1.575 in	 FT-NFM2S4
		 FT-S500		 FT-SFM2
		 FT-SN500		 FT-SNFM2

# Information of Discontinued Models

Thru-beam type fiber • Reflective type fiber (Changed to 2 m 6.562 ft free-cut type)

## Shape of fiber head

Type	Discontinued models		Recommended replacements	
	Shape of fiber head (mm in)	Model No.	Shape of fiber head (mm in)	Model No.
Reflective type fiber		<b>FD-500</b>		<b>FD-FM2</b>
		<b>FD-500S</b>		<b>FD-FM2S</b>
		<b>FD-500S4</b>		<b>FD-FM2S4</b>
		<b>FD-G500</b>		<b>FD-G4</b>
		<b>FD-N500</b>		<b>FD-NFM2</b>
		<b>FD-N500S</b>		<b>FD-NFM2S</b>
		<b>FD-N500S4</b>		<b>FD-NFM2S4</b>
		<b>FD-SN500</b>		<b>FD-SNFM2</b>
		<b>FD-SNM1SV2</b>		<b>FD-V41</b>
	Sleeve part cannot be bent.		Sleeve part cannot be bent.	